


# Concept Learning

Zhang Hongxin  
zhx@cad.zju.edu.cn

State Key Lab of CAD&CG, ZJU  
2006-03-23



# Overview



- Learning from examples
- General-to specific ordering of hypotheses
- Version spaces and candidate elimination algorithm
- Inductive bias

# Introduction



- What is concept learning?
  - Induce Boolean function from a sample of positive/negative training examples.
  - Infer the general definition of some concept, given examples labeled as members or nonmembers of the concept.
- Concept learning in daily life
  - 根据人证物证判断犯罪嫌疑人是否有罪
  - 根据笔试面试决定是否录用
  - And more ...



# A Demo Task – *Enjoy Sport*

- Concept:
  - days on which my friend Tom enjoys his favorite water sports
- Task:
  - predict the value of "Enjoy Sport" for an arbitrary day based on the values of the other attributes

## Training Data

Attributes	ID	Sky	Temp	Humidity	Wind	Water	Forecast	Enjoy
	1	Sunny	Warm	Normal	Strong	Warm	Same	Yes
	2	Sunny	Warm	High	Strong	Warm	Same	Yes
Example	3	Rainy	Cold	High	Strong	Warm	Change	No
	4	Sunny	Warm	High	Strong	Cool	Change	Yes



# Representing Hypothesis

- Hypothesis  $h$  is described as a conjunction of constraints on attributes
- Each constraint can be:
  - A specific value : e.g. Water=Warm
  - A don't care value : e.g. Water=?
  - No value allowed (null hypothesis): e.g. Water= $\emptyset$
- Example: hypothesis  $h$

	Sky	Temp	Humid	Wind	Water	Forecast	
<	Sunny	?	?	Strong	?	Same	>



# A Demo Task – *Enjoy Sport*


- **Given:**

- Instance Space  $X$ : Possible days described by the attributes=[Sky, Temp, Humidity, Wind, Water, Forecast]
- Target function  $c$ : Enjoy Sport  $X \rightarrow \{0,1\}$
- Hypotheses Space  $H$ :
  - conjunction of literals e.g.  $\langle \text{Sunny} \ ? \ ? \ \text{Strong} \ ? \ \text{Same} \ \rangle$
- Training examples  $D$ :
  - positive and negative examples of the target function,  $\langle x_1, c(x_1) \rangle, \dots, \langle x_n, c(x_n) \rangle$

- **Determine:**

- A hypothesis  $h$  in  $H$  such that  $h(\mathbf{x})=c(\mathbf{x})$  for all  $\mathbf{x}$  in  $X$ .

# The Inductive Learning Hypothesis



- Any hypothesis found to approximate the target function well over a sufficiently large set of training examples will also approximate the target function well over other unobserved examples.
- Find the hypothesis that best fits the training data
- 根据已知推断未知，假定已知满足某种规律

# Number of Instances, Concepts, Hypotheses



- ◆ Sky: sunny, cloudy, rainy
- ◆ Air Temp: warm, cold
- ◆ Humidity: normal, high
- ◆ Wind: strong, weak
- ◆ Water: warm, cold
- ◆ Forecast: same, change

#distinct instances :  $3*2*2*2*2*2 = 96$

#distinct concepts :  $2^{96}$

#syntactically distinct hypotheses :  $5*4*4*4*4*4=5120$

#semantically distinct hypotheses :  $1+4*3*3*3*3*3=973$



# Perspective



- Concept learning can be formulated as a **searching** - *through a predefined space of potential hypotheses for the hypothesis that **best fits** the training examples.*
- *General-to-specific* ordering

$$h_j \geq_g h_k \iff (\forall x \in X)[(h_k(x) = 1) \rightarrow (h_j(x) = 1)]$$

- Example :  $\langle \text{Sunny}, ?, ?, ?, ?, ? \rangle \geq \langle \text{Sunny}, ?, ?, \text{Strong}, ?, ? \rangle$
- Introduce a **hierarchy** structure into hypotheses space, which leads to efficient searching strategy.

# Algorithms



Algorithm	Order	Strategy	N/P
FIND-S	Specific-to-general	Top-down	Positive
LIST-THEN-ELIMINATE	General-to-Specific	Bottom-up	Negative
CANDIDATE-ELIMINATION	Bi-directional	Bi-directional	Both



# FIND-S

- $h_0 = \langle 0, 0, 0, 0, 0, 0 \rangle$
- $h_1 = \langle \text{Sunny, Warm, Normal, Strong, Warm, Same} \rangle$
- $h_2 = \langle \text{Sunny, Warm, ?, Strong, Warm, Same} \rangle$
- $h_3 = \langle \text{Sunny, Warm, ?, Strong, Warm, Same} \rangle$
- $h_4 = \langle \text{Sunny, Warm, ?, Strong, ?, ?} \rangle$

Training examples:

1.  $\langle \text{Sunny, Warm, Normal, Strong, Warm, Same} \rangle$ , Enjoy Sport = **Yes**
2.  $\langle \text{Sunny, Warm, High, Strong, Warm, Same} \rangle$ , Enjoy Sport = **Yes**
3.  $\langle \text{Rainy, Cold, High, Strong, Warm, Change} \rangle$ , Enjoy Sport = **No**
4.  $\langle \text{Sunny, Warm, High, Strong, Cool, Change} \rangle$ , Enjoy Sport = **Yes**

Report the ***most specific*** hypothesis



# LIST-THEN-ELIMINATE

- $h_0 = \langle ?, \quad ?, \quad ?, \quad ?, \quad ?, \quad ? \rangle$
- $h_1 = \langle \text{Sunny}, ?, \quad ?, \quad ?, \quad ?, \quad ? \rangle$  or  
 $\langle ?, \quad \text{Warm}, ?, \quad ?, \quad ?, \quad ? \rangle$  or  
 $\langle ?, \quad ?, \quad \text{Normal}, ?, \quad ?, \quad ? \rangle$  or  
 $\langle ?, \quad ?, \quad ?, \quad \text{Weak}, ?, \quad ? \rangle$  or  
 $\langle ?, \quad ?, \quad ?, \quad ?, \quad \text{Cold}, \quad ? \rangle$  or  
 $\langle ?, \quad ?, \quad ?, \quad ?, \quad ?, \quad \text{Same} \rangle$

Report the ***most general*** hypothesis



# CANDIDATE-ELIMINATION (1)

**S0:** {<0, 0, 0, 0, 0, 0>}



**S1:** {<Sunny, Warm, Normal, Strong, Warm, Same>}



**S2:** {<Sunny, Warm, ?, Strong, Warm, Same>}

**G0, G1, G2:** {<?, ?, ?, ?, ?, ?>}


Training examples:

1. <Sunny, Warm, Normal, Strong, Warm, Same>, Enjoy Sport = **Yes**
2. <Sunny, Warm, High, Strong, Warm, Same>, Enjoy Sport = **Yes**



# CANDIDATE-ELIMINATION (2)

**S2, S3:** {<Sunny, Warm, ?, Strong, Warm, Same>}



Training examples:

3. <Rainy, Cold, High, Strong, Warm, Change>, Enjoy Sport = **No**



# CANDIDATE-ELIMINATION (3)

**S3:** {<Sunny, Warm, ?, Strong, Warm, Same>}



**S4:** {<Sunny, Warm, ?, Strong, ?, ?>}

**G4:** {<Sunny, ?, ?, ?, ?, ?> <?, Warm, ?, ?, ?, ?>}




**G3:** {<Sunny, ?, ?, ?, ?, ?> <?, Warm, ?, ?, ?, ?> <?, ?, ?, ?, ?, Same>}

Training examples:

4. <Sunny, Warm, High, Strong, Cool, Change>, Enjoy Sport = **Yes**



# Final Version Space



Report the *version space* – all possible hypotheses

<Sunny,Warm,Normal,Strong,Cool,Change>

<Rainy,Cold,Normal,Light,Warm,Same>

<Sunny,Warm,Normal,Light,Warm,Same>

<Sunny,Cold,Normal,strong,Warm,Same>



# Remarks



- Convergence Condition
  - Noise Free (No Errors)
  - The target concept **DOES** exist in the searching hypotheses space ***H***
- What Training Example Should the Learner Request Next?
  - Satisfy half the hypotheses in the current version space
  - Fastest Convergence, Least Sample Needed, Best Uncertainty Elimination
- How Can Partially Learned Concepts Be Used?
  - Absolutely Accept <Sunny,Warm,Normal,Strong,Cool,Change>
  - Absolutely Deny <Rainy,Cold,Normal,Light,Warm,Same>
  - Pending
    - <Sunny,Warm,Normal,Light,Warm,Same>
    - <Sunny,Cold,Normal,strong,Warm,Same>

# Inductive Bias



- Bias Vs. Unbiase
- The Futility of Bias-Free Learning
  - Too large searching space
  - The convergence is impossible
  - Rational inference is impossible
- Inductive bias of CANDIDATE-ELIMINATION algorithm
  - The target concept  $c$  is contained in the given hypothesis space  $H$ .
  - Inductive System == Deductive System + ***Inductive Bias***

# Summary



- Concept learning can be cast as **Searching** through predefined hypotheses space.
- The **general-to-specific** partial ordering of hypotheses leads to efficient searching strategy, such as CANDIDATE-ELIMINATION algorithm.
- A practical concept learning methods must employ **inductive bias**. Otherwise, they can only classify the observed training examples.
- Version spaces and the CANDIDATE-ELIMINATION algorithm provide a useful **conceptual framework** for studying concept learning. However, their correctness rely on the noise-free training examples and the ability of provided hypotheses space to express the unknown target concepts.

# EnjoySport revisit




- **Given:**

- Instances  **$X$** : Possible days, each described by the attributes
  - *Sky* (*Sunny*, *Cloudy*, and *Rainy*)
  - *Temp* (*Warm* and *Cold*)
  - *Humidity* (*Normal* and *High*)
  - *Wind* (*Strong* and *Weak*)
  - *Water* (*Warm* and *Cool*)
  - *Forecast* (*Same* and *Change*)
- Hypotheses  **$H$** : Each hypothesis is described by a **conjunction** of constraints. These constraints may be “?” (any value), “0” (no value), or a specific value.

- **Determine:**

- A hypothesis  $h$  in  **$H$**  such that  $h(x) = c(x)$  for all  $x$  in  **$X$** .



Thank you